

Single Phase Smart Meter

TMCB 012 SMART



Range :

5-60 Amps

- > Real Time Interoperable for Communication Technology Swap (GPRS/RF/NB-IoT/Wi-Fi/BLE)
- > Programmable TOU/TOD
- > Multi-Vender HES Compatible
- > Smart AMI with Programmable Post/Pre-Payment and Net Metering Modes
- > Certified IS16444 Standard
- > Anti-Tampers and Tamper Alerts
- > Last Gasp and First Breath Indication before Power fail and Restoration)



MEASUREMENT

- > Accuracy : Class 1.0 (Direct Connected)
- > Compliance with IS 16444 Standards
- > Four Quadrant measurement
- > Single Phase 2 Wire 60A Load switch
- > Active and Apparent measurements both in Import and Export
- > 0.000001kWh Resolution measurement

VOLTAGE AND POWER SUPPLY

- > Voltage - 240V AC, Frequency - 50Hz (Standard) Power supply surge - 440V

CURRENT

CURRENT RANGES

- > Direct Connected Meters : 5-60A
- > Overcurrent : 30 times IMAX for 0.5 cycles
- Burden < 0.5VA
- > Operating Temperature 27°C
- > UC1 Load switch ranges 60A/90A/120A

SMART FEATURES

- > Alarms and alerts Alarm/alert for power on/off, over voltage and over current

Load control Disconnection provided for :

- > Over current and Over load conditions
- > For selected Tampers
- > Disconnection Signal from Utility
- > Relay Provided in both phase and neutral complying to IS15884 with UC1/UC2/UC3
- > Status available on display and data downloading
- > Connection/Disconnection are logged as events
- > Data security Multilevel Password for Data Reading and Programming
- > Communication Optical port for local communication with DLMS
- > NAN over 865-867 MHz RF complying to IS 15959 Part 2
- > GPRS Modem 2G/3G/4G/ NB-IoT

Pluggable Communication Module either GPRS-4G or RF which can be Swapped in the field without changing the Meter. The Meter has the Intelligence to detect automatically and start communicating seamlessly.

Smart Meters Supports all the Three Modes on real time. Once configured the Meter shall operate in any of the following Modes :

- 1. Post Payment Mode**
- 2. Pre-Payment Mode**
- 3. Net Metering Mode**

- > Load survey and Day survey as per standards
- > Neutral and Phase measurements
- > Programmable Block Window and Sliding Window MD Calculation methods
- > Programmable MD integration period and Reset dates
- > Active/Apparent Import and Export MD Registers

- > Burden < 10VA (as per IS 16444)
- > Power consumption = 5Watt (As per Standard)

Post Payment Mode : Meter can be configured with Time of Use (TOU) Tariff and programmable Bills dates. It Supports Monthly/Bi-Monthly/Odd Even Monthly Billing

Pre-Payment Mode : Complete Prepayment algorithm is built inside the Meter. The Meter handles the Prepayment Token Recharge either in kWh/Rupees and functions independently without the intervention from the server for disconnection. Supports Holiday, Happy Hours and TOU based deduction. Provision to deduct minimum usage, Different Tariffs for Load Limit Exceed and Emergency Credits.

Net Metering Mode : Measures both Import and Export separately and has the Net value available for both kWh and KVArh billing.

MEASURED ENERGY VALUES

- > Import/ Export/Net kWh and kVAh
- > Absolute kWh and kVAh

SYSTEM INTEGRATION SUPPORT

- > Interoperable DLMS compliance
- > Programmable Alarms and Instant/Load Survey/Day Survey/Tamper/Billing Push

ENVIRONMENTAL

- > Operating temperature range : -25°C to 60°C Limit range : -40°C to 70°C
- > Storage range : -40 to 80 deg C
- > Relative humidity : Up to 75% mean, 95% non condensing for 30 days
- > Ingress protection : IP51

MECHANICAL

- > Sealing : break-open sealing provision as per Standards
- > Material : Engineering plastic/ PC/ Brass terminals



38,39,40, Mahatma Gandhi Road, SIHS Colony, Coimbatore - 641 033, TN, (INDIA).

Contact : +91-422-2391534, +91 93631 05104, +91 93610 80382

E-Mail : customercare@technometers.in, rakesh.techno@gmail.com